



SUN-BATT-5.12R



DATASHEET

SUN-BATT-5.12R/BYD 100Ah Rack

Global Tech China Ltd, 3 Floor, Wai Yip Industrial Building.
171 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong.

Tel: +852 2884 4318 Fax: +8522884 4816

www.sunsynk.com / sales@sunsynk.com



Performance	
Nominal Voltage	51.2 Vdc
Nominal Capacity	100Ah
Battery Energy ¹	5120 Wh
Charge Voltage	55.68~56.16Vdc
Discharge Voltage	45.6-56.16 Vdc
Nominal Charge/Discharge Current	50A
Nominal Charge/Discharge Power	2500W
Max Charge / Discharge Current	100A
Max Charge / Discharge Power	5000W
Short Circuit Current	350A
Communication	
Display	SOC status indicator, LED indicator
Communication	RS232, RS485, CAN
General Specification	
Dimension(W×D×H mm)	440×550×130mm
Weight (Kg)	49kg
Installation	Rack-Mounted, Wall-Mounted or Cabinet-Mounted
Working Temperature ²	-20°C ~ 60°C
Storage Temperature	≤25°C, 12 months
	≤35°C, 6 months
	≤45°C, 3 months
Operating / Storage / humidity	≤ 95%RH
Max Operating Altitude	≤ 2000m
IP Rating	IP20
Cell Technology	LiFePO ₄ , Lithium-ion Phosphate
Cycle life ³	6000 Cycles @ 80% DOD / 25°C / 0.5C, 60% EOL
Scalability	Max 8 batteries in parallel
Warranty	5 years
Standard Compliance	
Certification	UN38.3, IEC62619, IEC61000, UL 1642(cell) (more available upon request)
Ordering and Deliverable Part	
Product ordering part	SUN-BATT-5.12R Battery SUN-BATT-5.12R Power cable SUN-BATT-5.12R Parallel cable



CONTACT US

Email us: sales@sunsynk.com Call us UK: +44 151 8324300

VAT Number: 175669460

UK Address: Sunsynk, 17 Turnstone business park,
Mulberry Avenue. Widnes, Cheshire, WA8 0WN.

GlobalTech Ltd

